



TITAN

PERFORMANCE LUBRICANTS

HIGH MILEAGE SYNTHETIC BLEND PASSENGER CAR MOTOR OILS

TITAN PERFORMANCE High Mileage Motor Oil for passenger cars provides maximum protection for longer engine life in vehicles with over 75,000 miles. The formulation contains extra additives to help stop leaks and reduce oil consumption by conditioning seals and gaskets. Plus, it reduces sludge and damaging deposits.

TITAN PERFORMANCE High Mileage Synthetic Blend Motor Oils are specially formulated with Group II+ and Group III base oils plus state-of-the-art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20, 5W-30, and 10W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

TITAN PERFORMANCE PROPERTIES

SAE VISCOSITY GRADES	5W-20	5W-30	10W-30
API Service	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C	51.6	65.7	65.1
cSt @ 100°C	8.8	10.9	10.1
Viscosity Index	150	158	141
CCS Viscosity			
cSt @ -30°C	6000	6200	-
cSt @ -25°C	-	-	6200
Evaporative Loss, NOACK, wt%	< 15	< 15	< 15
Specific Gravity @ 15°C (60°F)	0.858	0.860	0.861
Flash Point, °C	220	220	220
Pour Point, °C	-44	-44	-40
Color (ASTM)	L 3.0	L 3.0	L 3.0

For additional qualifications, please contact your TITAN PERFORMANCE Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 08/17