



TITAN

PERFORMANCE LUBRICANTS

dexos1™ Gen 2 FULL SYNTHETIC PASSENGER CAR MOTOR OIL

TITAN PERFORMANCE Full Synthetic dexos1™ Gen 2 Passenger Car Motor Oil is engineered using high performance additives to provide superior wear protection, improve fuel economy, perform under extreme conditions (low and high temperatures), and extend engine life. It is designed to keep engines clean by fighting sludge, providing oxidation control, and protect your engine against low speed pre-ignition (LSP) in turbo-charged gasoline direct injection engines (TGDI). It also meets the API SN and ILSAC GF-5 specifications.

TITAN PERFORMANCE PROPERTIES		
SAE Viscosity Grade	0W-20	5W-30
GM Approved	dexos1™ Gen 2	dexos1™
API Service	SN	Gen 2 SN
ILSAC	GF-5	GF-5
Kinematic Viscosity cSt @ 100°C cSt @ 40°C	8.3 44.2	10.9 61.1
Viscosity Index	166	172
CCS Viscosity cP @ -35°C cP @ -30°C	5600 -	- 4000
MRV Viscosity cP @ -40°C cP @ -35°C	< 40000 -	- < 40000
Evaporative Loss, NOACK, wt%	< 13	< 13
Specific Gravity @ 15°C (60°F)	0.846	0.847
Flash Point, °C	226	228
Pour Point, °C	-42	-39
Color (ASTM)	3.0	3.0
Sulfated Ash, wt%	< 1.0	< 1.0

For additional qualifications, please contact your TITAN PERFORMANCE Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 08/17